

LEED-Existing Building

Sustainability By
Resurfacing Existing Ceiling Tiles and Grid Systems



BEFORE



AFTER

APPLICATIONS:

Department Stores, Supermarkets, Office Suites & Hallways, Schools, Libraries, Drug Stores, Restaurants, Hospitals, Banks... *Wherever acoustic ceilings are found!*

Green Building Rating System For Commercial Interiors

LEED for Retail - Commercial Interiors Pilot Version 1.0

<http://www.usgbc.org/ShowFile.aspx?DocumentID=2618>

Credit 1.2 LEED® for Retail - Commercial Interiors Retail 2007 45

Building Reuse, Maintain 40% or 60% of Interior Non-Structural Components

1 point for 40% 2 points for 60%

Intent

Extend the life cycle of existing building stock, conserve resources, retain cultural resources, reduce waste and reduce environmental impacts of new buildings as they relate to materials manufacturing and transport.

Requirements

Maintain at least 40% by area of the existing non-shell, non-structure components (walls, flooring and ceilings). 1 POINT

Maintain at least 60% by area of the existing non-shell, non-structure components (walls, flooring and ceilings). 2 POINTS

Potential Technologies & Strategies

Identify during the selection and design of the tenant space the potential to maintain as many of the existing interior elements as possible. Remove elements that pose contamination risk to occupants and update outdated components. Quantify the extent of reuse.



ReCEIL It International, Inc.
1-800-CEILING
Tel: 631-842-0099
Fax: 631-980-7668
www.receilit.com
Email: info@receilit.com